Technical Specifications

V-420 Dynamic Noise Canceling Microphone

- Low impedance
- Dynamic element
- Soft lip guard
- Cycolac housing
- Heavy duty four conductor shielded cable
- Push to talk lever
- Indoor use



Hand held

Description:
The V-420 Dynamic Noise Canceling Microphone is a paging microphone with dynamic noise canceling technology. The V-420 features a handheld design with a press-to-talk lever. The V-420 is ideal for restaurants, retail stores, bowling alleys, offices, transportation terminals and dispatch centers.

SPECIFICATIONS

ELEMENT
Dynamic

OUTPUT
Output Level: -58 dB (Ref. 0 dB = 1 mw/10 microbars)
Output Impedance: Lo Z, 200 Ohms

FREQUENCY RESPONSE
100 to 5 kHz

CONTROLS
Push-to-Talk button

HOUSING AND FINISH
Molded cycolac in black

DIMENSIONS AND WEIGHT
3.94in H x 2.97in W x 2.63in D
(10.00cm x 7.54cm x 6.68cm)
Weight: 0.63lbs (0.29kg)
Shipping Weight: 2.80lbs (1.26kg)

ARCHITECTS AND ENGINEERS

The Dynamic Noise Canceling Microphone, model V-420, shall consist of a dynamic microphone, a push-to-talk lever, a soft lip guard, heavy duty four conductor shielded cable.

The V-420 Dynamic Noise Canceling Microphone shall have a frequency response of 100 to 5 kHz. The impedance of the V-420 microphone shall be 200 Ohm. The sensitivity of the microphone shall be -58 dB (Ref. 0 dB = 1 mw/10 microbars).
.
The V-420 Dynamic Noise Canceling Microphone shall be constructed of molded cycolac and finished in black. The V-420 shall be suitable for indoor applications.

Maximum dimensions shall be: 3.94in H x 2.97in W x 2.63in D (10.00cm x 7.54cm x 6.68cm). Weight shall be approximately: 0.63lbs (0.29kg).

Warranty information may be found on our website at www.valcom.com/warranty.

2022 Rev. 1.8.4