



**RUST-OLEUM® PROFESSIONAL FLOORING UNIVERSAL TINT PACKS**

**DESCRIPTION AND USES**

Use Rust-Oleum® Professional Flooring Universal Tint Packs to pigment epoxy, polyurethane, alkyd, and polyaspartic floor coatings. Formulated using proprietary technology, these bio-based universal tint packs offer advanced color accuracy and colorant stability, with the flexibility to use across multiple floor coating chemistries. Professional Flooring Universal Tint Packs are available in 19 standard colors, a custom color option, and two sizes to meet the most demanding jobsite color requirements.

**PRODUCT FEATURES**

- For use in most solvent-based floor coating technologies
- Low VOC
- Excellent Pigment Development
- Minimal effect on coating performance
- Freeze / Thaw Stable above 30°F
- Resists colorant flood/float/flocculation
- Viscosity stability for 2 years
- Will not gel or crystalize
- Environmentally conscious

**PRODUCTS**

16 Oz.	48 Oz.	DESCRIPTION
373756	373844	Black
373757	373845	Dark Gray
373828	373846	Dark Green
373829	373847	Dunes Tan
373830	373848	Light Gray
373831	373849	Navy Gray
373832	373850	Greige
373833	373851	Safety Blue
373834	373852	Safety Orange
373835	373853	Safety Red
373836	373854	Safety Yellow
373837	373855	Safety Green
373838	373856	Sahara Desert
373839	373857	Sand
373840	373858	Silver Gray
373841	373859	Super Light Gray
373842	373860	Tile Red
373843	373861	White
366981	380277	Custom

**PRODUCT APPLICATION**

**APPLICATION**

Pre-mix Universal Tint Packs prior to adding into floor coatings. Hand mixing until uniform in appearance is acceptable.

Add Universal Tint Packs at 8 oz. per gallon of mixed floor coating material and combine thoroughly via power mix to achieve uniform colorant dispersal.

**NOTE:** Some colors, including safety colors, may require additional coats if desired coverage is not achieved in the first application.

**NOT FOR USE IN WATER BASED COATINGS**

• TRUSTED QUALITY SINCE 1921 •



**RUST-OLEUM® PROFESSIONAL FLOORING UNIVERSAL TINT PACKS**

**PHYSICAL PROPERTIES**

		PROFESSIONAL FLOORING UNIVERSAL TINT PACKS
<b>Resin Type</b>		Proprietary Bio Based
<b>Pigment Type</b>		Inorganic and organic
<b>Solvents</b>		NA
<b>Weight</b>	<b>Per Gallon</b>	8.42-19.02 lbs.
	<b>Per Liter</b>	1.01-2.28 kg
<b>Solids</b>	<b>By Weight</b>	13.6-72.9%
	<b>By Volume</b>	22.7-23.1%
<b>Volatile Organic Compounds</b>		<10 g/l
<b>Mixing Ratio</b>		8 oz.- per gallon
<b>Shelf Life</b>		2 years
<b>Flash Point</b>		>200° F
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.