

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier Sonax Profiline Ceramic Coating CC 36 Gloss Coat (2)

Other means of identification 2369410-745 (02230000-745)

SynonymsNot available.Recommended useCoatingsRecommended restrictionsNone known.Manufacturer informationSonax GmbH

Münchener Strasse 75 D-86633 Neuburg/Donau DE Phone: 0049 84 31 53-0

24-Hour-Number: GBK/Infotrac ID 91785:

(USA domestic) 1 800 535 5053

Supplier Vision Investments, LLC

4565 W. 16th Street Indianapolis, IN 46222 Courriel: info@sonaxusa.com Téléphone: 1-317-295-7056

2. Hazards Identification

Physical hazards Gases under pressure Liquefied gas

Health hazards Not classified.
Environmental hazards Not classified.
WHMIS 2015 defined hazards Not classified

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Protect from sunlight. Store in a well-ventilated place.

Disposal Dispose of waste and residues in accordance with local authority requirements.

WHMIS 2015: Health Hazard(s)

not otherwise classified

(HHNOC)

None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)

None known

Hazard(s) not otherwise

classified (HNOC)

hydrotreated

None known.

Supplemental information None.

3. Composition/Information on Ingredients

MixtureChemical nameCommon name and synonymsCAS number%Distillates (petroleum), hydrotreated middle64742-46-72.06Carbon dioxide124-38-91.97Distillates (petroleum), light64742-47-80.88

#28756 Page: 1 of 10 Issue date 30-November-2017

4. First Aid Measures

If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention. Inhalation

Direct contact with eyes may cause temporary irritation.

Skin contact Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.

> Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.

Ingestion Not likely, due to the form of the product. Do not induce vomiting. If vomiting occurs naturally, have

victim lean forward to reduce risk of aspiration.

Most important

delayed

Eye contact

symptoms/effects, acute and

General information If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show

this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of

reach of children.

5. Fire Fighting Measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire-fighting equipment/instructions

Specific methods

General fire hazards **Hazardous combustion**

products

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Not available.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. In the event of fire, cool product with water spray.

Use standard firefighting procedures and consider the hazards of other involved materials. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

None known.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Emergency personnel need self-contained breathing equipment. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Isolate area until gas has dispersed. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see

section 13 of the SDS.

Environmental precautions Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Provide adequate ventilation.

Observe good industrial hygiene practices.

When using do not eat or drink.

Conditions for safe storage, including any incompatibilities Store in a cool, dry place out of direct sunlight. Store in original tightly closed container.

Store in a well-ventilated place.

STEL

Store away from incompatible materials (see Section 10 of the SDS).

Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Form Components Type Value

Carbon dioxide (CAS 124-38-9)

54000 mg/m3

Canada. Alberta OELs (Occupation Components	Туре	Value	Form
		30000 ppm	
	TWA	9000 mg/m3 5000 ppm	
Distillates (petroleum), nydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Vapor.
Canada. British Columbia OELs. (0 Safety Regulation 296/97, as amen	ded)		•
Components	Туре	Value	Form
Carbon dioxide (CAS 24-38-9)	STEL	15000 ppm	
	TWA	5000 ppm	
Distillates (petroleum), ydrotreated middle (CAS 14742-46-7)	TWA	1 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Canada. Manitoba OELs (Reg. 217 Components	/2006, The Workplace Safety A Type	nd Health Act) Value	Form
Carbon dioxide (CAS	STEL	30000 ppm	
24-38-9)			
	TWA	5000 ppm	
Distillates (petroleum), ydrotreated middle (CAS 4742-46-7)	TWA	5 mg/m3	Inhalable fraction.
Canada. Ontario OELs. (Control of Components	Exposure to Biological or Che Type	emical Agents) Value	
Carbon dioxide (CAS	STEL	30000 ppm	
24-38-9)			
	TWA	5000 ppm	
Canada. Quebec OELs. (Ministry o Components	f Labor - Regulation Respectir Type	ng the Quality of the Work Env Value	ironment) Form
Carbon dioxide (CAS	STEL	54000 mg/m3	
24-38-9)		· ·	
	T\\/	30000 ppm	
	TWA	9000 mg/m3 5000 ppm	
Distillates (petroleum), hydrotreated middle (CAS 14742-46-7)	STEL	10 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	1590 mg/m3	
···· · <u>·</u> ··· · · · · · · · · · · · · ·		400 ppm	
JS. OSHA Table Z-1 Limits for Air			_
Components	Туре	Value	Form
Carbon dioxide (CAS 24-38-9)	PEL	9000 mg/m3	
2.000)		5000 ppm	
Distillates (petroleum), hydrotreated middle (CAS 14742-46-7)	PEL	5 mg/m3	Mist.

Components	Туре		Value	Form
			400 mg/m3	
			100 ppm	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	PEL		400 mg/m3	
•			100 ppm	
US. ACGIH Threshold Limit	Values			
Components	Туре		Value	Form
Carbon dioxide (CAS 124-38-9)	STEL		30000 ppm	
	TWA		5000 ppm	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA		5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to			Value	Form
Components	Туре			TOTHI
Carbon dioxide (CAS 124-38-9)	STEL		54000 mg/m3	
			30000 ppm	
	TWA		9000 mg/m3	
			5000 ppm	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL		10 mg/m3	Mist.
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA		100 mg/m3	
logical limit values	No biological exposure limit	ts noted for the ingredier	nt(s).	
osure guidelines		· ·	,	
Canada - Alberta OELs: Ski	n designation			
Distillates (petroleum), lig 64742-47-8)	tht hydrotreated (CAS	Can be absorbed the	hrough the skin.	
Canada - British Columbia	DELs: Skin designation			
Distillates (petroleum), lig 64742-47-8)		Can be absorbed the	hrough the skin.	
Canada - Saskatchewan OE	-	0 1 1 1 1		
Distillates (petroleum), lig	ht hydrotreated (CAS Can be absorbed through the skin. Ensure adequate ventilation.			
oropriate engineering trols	Ensure adequate ventilation	n.		
vidual protection measures,	such as personal protective	e equipment		
Eye/face protection	Safety goggles or glasses.			
Skin protection				
Hand protection	Rubber gloves. Confirm with a reputable supplier first.			
Other	As required by employer code.			
Respiratory protection	Not normally required if good ventilation is maintained.			
Thermal hazards	Not applicable.			
neral hygiene siderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.			
	9. Physical and	I Chemical Propert	ties	
pearance	Aerosol			
rainal atata	Coo			

Odor	Characteristic
Odor threshold	Not available.

Gas.

Aerosol White

Physical state

Form

Color

Not available. pН Not available. Melting point/freezing point

Initial boiling point and boiling

range

212 - 532.4 °F (100 - 278 °C) Active ingredient data

Pour point Not available. Specific gravity Not available. **Partition coefficient** Not available.

(n-octanol/water)

Flash point Not applicable. Not available. **Evaporation rate** Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

(%)

Not available.

Flammability limit - upper

Flammability limit - lower

Not available.

(%)

Not available. **Explosive limit - lower (%)** Explosive limit - upper (%) Not available. Not available. Vapor pressure Vapor density Not available.

Relative density 0.97 - 0.98 g/cm3 Active ingredient data

Solubility(ies) Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available.

Viscosity > 20.5 mm²/s Active ingredient data

Other information

Not explosive. **Explosive properties** Not oxidizing **Oxidizing properties**

10. Stability and Reactivity

May react with incompatible materials. Reactivity

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Chemical stability Material is stable under normal conditions. Heat. Do not mix with other chemicals. Conditions to avoid

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological Information

Eye, Skin contact, Inhalation, Ingestion. Routes of exposure

Information on likely routes of exposure

May cause stomach distress, nausea or vomiting. Ingestion

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation. Symptoms related to the

physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components **Species Test Results**

Carbon dioxide (CAS 124-38-9)

Acute Inhalation

LC50 Not available

Page: 5 of 10 #28756 Issue date 30-November-2017

Test Results Components **Species** Oral LD50 Not available Distillates (petroleum), hydrotreated middle (CAS 64742-46-7) Acute Dermal LD50 Rabbit > 2000 mg/kg, 24 Hours, ECHA 2000 mg/kg, Madison Chemical Inhalation LC50 Rat 73680 mg/L, 4 Hours, HSDB 7640 mg/m³, 4 h, ECHA 7640 mg/m3, 4 Hours, ECHA 61 mg/L, 4 Hours, HSDB 4.6 mg/L, 4 Hours, ECHA 1.8 mg/L, 4 Hours, ECHA 1.8 mg/L, 4 Hours, ECHA 1.7 mg/L, 4 Hours, ECHA Oral Rat LD50 > 5000 mg/kg, ECHA > 25 ml/kg, HSDB 7400 mg/kg, LOLI Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Acute Dermal LD50 Rabbit > 4000 mg/kg, 24 Hours, ECHA > 2000 mg/kg > 2000 mg/kg, 24 Hours, ECHA Inhalation LC50 Cat > 6.4 mg/L, 6 Hours, ECHA Rat > 7.5 mg/L, 6 Hours, ECHA > 6 mg/L, 4 Hours, ECHA > 5.7 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA > 4.6 mg/L, 4 Hours, ECHA > 4.5 mg/L, 4 Hours, ECHA > 4.3 mg/L, 4 Hours, ECHA > 0.1 mg/L, 8 Hours, ECHA 5.2 mg/l/4h, LOLI Oral LD50 Rat > 20000 mg/kg, ECHA > 5000 mg/kg, LOLI > 25 ml/kg Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Not available. **Exposure minutes** Not available. Erythema value Not available. Oedema value Serious eye damage/eye Direct contact with eyes may cause temporary irritation. irritation Not available. Corneal opacity value Not available. Iris lesion value

Conjunctival reddening

value

Not available.

Not available. Conjunctival oedema value Recover days Not available.

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity See below.

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated middle (CAS Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity

64742-46-7) to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Teratogenicity Not available. Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components Species **Test Results**

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/L, 48 hours Fish LC50 Rainbow trout, donaldson trout 8.8 mg/L, 96 hours

(Oncorhynchus mykiss)

8.8 mg/L, 96 hours

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

Aquatic

Crustacea EC50 2.7 - 5.1 mg/L, 48 hours Water flea (Daphnia pulex) Fish LC50 Rainbow trout, donaldson trout 2.9 mg/L, 96 hours

(Oncorhynchus mykiss)

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. Mobility in soil No data available. Not available. Mobility in general

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal instructions**

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Page: 7 of 10 #28756 Issue date 30-November-2017

14. Transport Information

Transport of Dangerous Goods In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods

Regulations, we certify that the classification of this product is correct as of the SDS date of issue. (TDG) Proof of Classification

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number UN1950

Proper shipping name Aerosols, non-flammable,

Hazard class

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number UN1950

Proper shipping name AEROSOLS, non-flammable

2.2 Hazard class **Special provisions** 80.107

DOT



TDG



15. Regulatory Information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada CEPA Schedule I: Listed substance

Carbon dioxide (CAS 124-38-9) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Distillates (petroleum), hydrotreated middle (CAS 1 TONNES

64742-46-7)

Distillates (petroleum), light hydrotreated (CAS 1 TONNES

64742-47-8)

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Carbon dioxide (CAS 124-38-9) **Precursor Control Regulations**

Not regulated.

WHMIS 2015 Exemptions Not applicable

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

See below

US - California Hazardous Substances (Director's): Listed substance

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), light hydrotreated (CAS Listed. 64742-47-8)

US - Minnesota Haz Subs: Listed substance

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), light hydrotreated (CAS Listed. 64742-47-8)

US - New Jersey RTK - Substances: Listed substance

Carbon dioxide (CAS 124-38-9)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Carbon dioxide (CAS 124-38-9)

US - Texas Effects Screening Levels: Listed substance

Alkanes, C9- 12-iso- (CAS 90622-57-4)

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), hydrotreated middle (CAS Listed. 64742-46-7)

Listed.

Distillates (petroleum), light hydrotreated (CAS Listed.

64742-47-8)

US. Massachusetts RTK - Substance List

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon dioxide (CAS 124-38-9)

Distillates (petroleum), light hydrotreated (CAS 64742-47-8)

US. Rhode Island RTK

Carbon dioxide (CAS 124-38-9)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0





Disclaimer

Issue date

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

30-November-2017

Version #

Effective date 30-November-2017

Prepared by Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

Other information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the

document.