

1. Product and Company Identification

| | |
|--------------------------------------|--|
| Product identifier | Sonax Leather Foam |
| Other means of identification | 02893000-755 |
| Synonyms | Not available. |
| Recommended use | Car care. |
| Recommended restrictions | None known. |
| Manufacturer information | Sonax GmbH Münchener Strasse 75 D-86633 Neuburg/Donau DE Phone: 0049 84 31 53-0 24-Hour-Number: GBK/Infotrac ID 91785: (USA domestic) 1 800 535 5053 |
| Supplier | Vision Investments, LLC 4565 W. 16th Street Indianapolis, IN 46222 US Email: info@sonaxusa.com Phone: 1-317-295-7056 |

2. Hazards Identification

| | | |
|-----------------------------------|--|-----------------------------|
| Physical hazards | Flammable aerosols Gases under pressure | Category 1 Liquefied gas |
| Health hazards | Not classified. | |
| Environmental hazards | Not classified. | |
| WHMIS 2015 defined hazards | Not classified | |
| Label elements | | |



| | | |
|--|---|--|
| Signal word | Danger | |
| Hazard statement | Extremely flammable aerosol. Contains gas under pressure; may explode if heated. | |
| Precautionary statement | | |
| Prevention | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. | |
| Response | Wash hands after handling. | |
| Storage | Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. | |
| Disposal | Dispose of waste and residues in accordance with local authority requirements. | |
| WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) | None known | |
| WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) | None known | |
| Hazard(s) not otherwise classified (HNOC) | None known. | |
| Supplemental information | None. | |

3. Composition/Information on Ingredients

Mixture

| Chemical name | Common name and synonyms | CAS number | % |
|---------------|--------------------------|------------|---------|
| Butane | | 106-97-8 | 1 - 5 * |

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|----------|
| Naphtha (petroleum), hydrotreated heavy | | 64742-48-9 | 5 - 10 * |
| Propane | | 74-98-6 | 1 - 5 * |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments *CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.
US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

| | |
|---|--|
| Inhalation | If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention. |
| Skin contact | Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists. |
| Eye contact | Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists. |
| Ingestion | Not likely, due to the form of the product. Do not induce vomiting. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Treat patient symptomatically. |
| General information | If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children. |

5. Fire Fighting Measures

| | |
|--|--|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide. |
| Unsuitable extinguishing media | None known. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. |
| Special protective equipment and precautions for firefighters | Not available. |
| Fire-fighting equipment/instructions | Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. |
| Hazardous combustion products | May include and are not limited to: Oxides of carbon. |

6. Accidental Release Measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Before attempting clean up, refer to hazard data given above. Remove sources of ignition. Although the chance of a significant spill or leak is unlikely in aerosol containers, in the event of such an occurrence, absorb spilled material with a non-flammable absorbent such as sand or vermiculite. Isolate area until gas has dispersed. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Do not discharge into lakes, streams, ponds or public waters. |

7. Handling and Storage

| | |
|--------------------------------------|---|
| Precautions for safe handling | Pressurized container: Do not pierce or burn, even after use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only in well-ventilated areas. Observe good industrial hygiene practices. Wash thoroughly after handling. When using do not eat or drink. |
|--------------------------------------|---|

Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F.
 Keep away from heat, sparks and open flame.
 Store in a well-ventilated place.
 Store away from incompatible materials (see Section 10 of the SDS).
 Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

| Components | Type | Value |
|--|------|------------------------|
| Butane (CAS 106-97-8) | TWA | 1000 ppm |
| Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) | TWA | 1590 mg/m ³ |
| | | 400 ppm |
| Propane (CAS 74-98-6) | TWA | 1000 ppm |

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Type | Value |
|-----------------------|------|----------|
| Butane (CAS 106-97-8) | STEL | 750 ppm |
| | TWA | 600 ppm |
| Propane (CAS 74-98-6) | TWA | 1000 ppm |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| Components | Type | Value |
|-----------------------|------|----------|
| Butane (CAS 106-97-8) | STEL | 1000 ppm |

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

| Components | Type | Value |
|--|------|-----------------------|
| Butane (CAS 106-97-8) | TWA | 800 ppm |
| Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) | TWA | 525 mg/m ³ |
| Propane (CAS 74-98-6) | TWA | 1000 ppm |

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

| Components | Type | Value |
|--|------|------------------------------------|
| Butane (CAS 106-97-8) | TWA | 1900 mg/m ³ 800 ppm |
| Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) | TWA | 1590 mg/m ³ 400 ppm |
| Propane (CAS 74-98-6) | TWA | 1800 mg/m ³ 1000 ppm |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|--|------|------------------------------------|
| Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) | PEL | 400 mg/m ³ 100 ppm |
| Propane (CAS 74-98-6) | PEL | 1800 mg/m ³ 1000 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|-----------------------|------|----------|
| Butane (CAS 106-97-8) | STEL | 1000 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|-----------------------|------|-----------------------------------|
| Butane (CAS 106-97-8) | TWA | 1900 mg/m ³ 800 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|--|--|---|
| Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) | TWA | 400 mg/m ³ |
| Propane (CAS 74-98-6) | TWA | 100 ppm 1800 mg/m ³ 1000 ppm |
| Biological limit values | No biological exposure limits noted for the ingredient(s). | |
| Appropriate engineering controls | Ensure adequate ventilation. | |
| Individual protection measures, such as personal protective equipment | | |
| Eye/face protection | Not normally required when used as directed. | |
| Skin protection | | |
| Hand protection | Not normally required when used as directed. | |
| Other | Not normally required. | |
| Respiratory protection | Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2). | |
| Thermal hazards | Not applicable. | |
| General hygiene considerations | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. | |

9. Physical and Chemical Properties

| | |
|---|---|
| Appearance | Aerosol |
| Physical state | Gas. |
| Form | Liquefied gas. |
| Color | Beige |
| Odor | Characteristic |
| Odor threshold | Not available. |
| pH | 6.5 - 7.5 @ 20C |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | 212 - 374 °F (100 - 190 °C) |
| Pour point | Not available. |
| Specific gravity | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Flash point | Not available. |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | Fully miscible |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | 12 - 16 s Flow Time @20°C (DIN EN ISO 2431/4mm) |

Other information

| | |
|----------------------|-------------------------------|
| Density | 0.96 - 0.97 g/cm ³ |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |

10. Stability and Reactivity

| | |
|------------------------------------|---|
| Reactivity | May react with incompatible materials. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Chemical stability | Material is stable under normal conditions. |
| Conditions to avoid | Heat. Do not mix with other chemicals. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | May include and are not limited to: Oxides of carbon. |

11. Toxicological Information

| | |
|--|--|
| Routes of exposure | Eye, Skin contact, Inhalation, Ingestion. |
| Information on likely routes of exposure | |
| Ingestion | May cause stomach distress, nausea or vomiting. |
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Symptoms related to the physical, chemical and toxicological characteristics | Direct contact with eyes may cause temporary irritation. |

Information on toxicological effects**Acute toxicity**

| Components | Species | Test Results |
|--|---------------|--|
| Butane (CAS 106-97-8) | | |
| Acute | | |
| Dermal | | |
| LD50 | Not available | |
| Inhalation | | |
| LC50 | Mouse | 539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 680 mg/L, 2 Hours, HSDB 57 %, 120 Minutes, ECHA 52 %, 120 Minutes |
| | Rat | > 800000 ppm, 10 Minutes, ECHA 1442738 mg/m ³ , 10 Minutes, ECHA 1354944 mg/m ³ , 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 276000 ppm, 4 Hours, CCOHS 1443 mg/L, 10 Minutes, ECHA 1355 mg/L, 10 Minutes |
| Oral | | |
| LD50 | Not available | |
| Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 6000 mg/kg, 24 Hours, ECHA > 3750 mg/kg, 24 Hours, ECHA > 3000 mg/kg, 24 Hours, ECHA |

| Components | Species | Test Results |
|-------------------|---------|------------------------------|
| | | > 2000 mg/kg, ECHA |
| | | > 2000 mg/kg, 24 Hours, ECHA |
| | | > 1900 mg/kg, 24 Hours, ECHA |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 8530 mg/m3, 4 Hours, ECHA |
| | | > 7970 mg/m3, 4 Hours, ECHA |
| | | > 7630 mg/m3, 4 Hours, ECHA |
| | | > 7300 mg/m3, 4 Hours, ECHA |
| | | > 5830 mg/m3, 4 Hours, ECHA |
| | | > 5740 mg/m3, 4 Hours, ECHA |
| | | > 5610 mg/m3, 4 Hours, ECHA |
| | | > 5470 mg/m3, 4 Hours, ECHA |
| | | > 5300 mg/m3, 4 Hours, ECHA |
| | | > 5280 mg/m3, 4 Hours, ECHA |
| | | > 5260 mg/m3, 4 Hours, ECHA |
| | | > 5250 mg/m3, 4 Hours, ECHA |
| | | > 5240 mg/m3, 4 Hours, ECHA |
| | | > 5220 mg/m3, 4 Hours, ECHA |
| | | > 5200 mg/m3, 4 Hours, ECHA |
| | | > 5170 mg/m3, 4 Hours, ECHA |
| | | > 5160 mg/m3, 4 Hours, ECHA |
| | | > 5100 mg/m3, 4 Hours, ECHA |
| | | > 5080 mg/m3, 4 Hours, ECHA |
| | | > 5050 mg/m3, 4 Hours, ECHA |
| | | > 5040 mg/m3, 4 Hours, ECHA |
| | | > 5020 mg/m3, 4 Hours, ECHA |
| | | > 5000 mg/m3, 4 Hours, ECHA |
| | | > 4980 mg/m3, 4 Hours, ECHA |
| | | > 4970 mg/m3, 4 Hours, ECHA |
| | | > 4420 mg/m3, 4 Hours, ECHA |
| | | > 5.4 mg/L, 4 Hours, ECHA |
| | | > 5.1 mg/L, 4 Hours, ECHA |
| | | > 5.1 mg/L, 4 Hours, ECHA |
| | | > 5 mg/L, 4 Hours, ECHA |
| | | > 5 mg/L, 4 Hours, ECHA |
| | | >= 5060 mg/m3, 4 Hours, ECHA |
| <i>Oral</i> | | |
| LD50 | Rat | > 7000 mg/kg, ECHA |
| | | > 6000 mg/kg, ECHA |
| | | > 5570 mg/kg, ECHA |
| | | > 5200 mg/kg, ECHA |
| | | > 5000 mg/kg, ECHA |
| | | > 4800 mg/kg, ECHA |
| | | > 4500 mg/kg, ECHA |
| | | > 25 ml/kg, HSDB |
| | | 14063 mg/kg, ECHA |
| | | 6620 mg/kg, ECHA |
| | | 5800 mg/kg, ECHA |
| | | 5390 mg/kg, ECHA |

| Components | Species | Test Results |
|---|--|---|
| | | 4820 mg/kg, ECHA |
| Propane (CAS 74-98-6) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Not available | |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 57 %, 120 Minutes, ECHA 52 %, 120 Minutes |
| | Rat | > 12000000 ppm, 4 hours > 800000 ppm, 10 Minutes, ECHA > 1464 mg/L, 15 Minutes, HSDB 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 1355 mg/L, 10 Minutes |
| <i>Oral</i> | | |
| LD50 | Not available | |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Exposure minutes | Not available. | |
| Erythema value | Not available. | |
| Oedema value | Not available. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | |
| Corneal opacity value | Not available. | |
| Iris lesion value | Not available. | |
| Conjunctival reddening value | Not available. | |
| Conjunctival oedema value | Not available. | |
| Recover days | Not available. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Contains < 3% (w/w) DMSO-extract See below. | |
| US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | Not listed. | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. | |
| Teratogenicity | Not available. | |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not likely, due to the form of the product. | |
| Chronic effects | Prolonged inhalation may be harmful. | |

12. Ecological Information

| | |
|--------------------|-----------|
| Ecotoxicity | See below |
|--------------------|-----------|

Ecotoxicological data

| Components | Species | | Test Results |
|--|---|--|--------------------------|
| Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (<i>Daphnia pulex</i>) | 2.7 - 5.1 mg/L, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>) | 8.8 mg/L, 96 hours |
| | | | 8.8 mg/L, 96 hours |
| Persistence and degradability | No data is available on the degradability of this product. | | |
| Bioaccumulative potential | | | |
| Mobility in soil | No data available. | | |
| Mobility in general | Not available. | | |
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation) | | |

13. Disposal Considerations

| | |
|--|--|
| Disposal instructions | Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. |

14. Transport Information

| | |
|---|--|
| Transport of Dangerous Goods (TDG) Proof of Classification | Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below. |
|---|--|

U.S. Department of Transportation (DOT)**Basic shipping requirements:**

| | |
|-----------------------------|--|
| UN number | UN1950 |
| Proper shipping name | Aerosols, flammable, (each not exceeding 1 L capacity) |
| Hazard class | 2.1 |
| Special provisions | N82 |
| Packaging exceptions | 306 |

Transportation of Dangerous Goods (TDG - Canada)**Basic shipping requirements:**

| | |
|-----------------------------|---------------------|
| UN number | UN1950 |
| Proper shipping name | AEROSOLS, flammable |
| Hazard class | 2.1 |
| Special provisions | 80, 107 |

DOT



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada DSL Challenge Substances: Listed substance

Butane (CAS 106-97-8) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Butane (CAS 106-97-8) 1 TONNES

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) 1 TONNES

Propane (CAS 74-98-6) 1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Controlled

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-4-isothiazolin-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8) Listed.

Propane (CAS 74-98-6) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US state regulations See below

US - California Hazardous Substances (Director's): Listed substance

Butane (CAS 106-97-8) Listed.

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

US - Illinois Chemical Safety Act: Listed substance

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US - Louisiana Spill Reporting: Listed substance

Butane (CAS 106-97-8) Listed.

Propane (CAS 74-98-6) Listed.

US - Minnesota Haz Subs: Listed substance

Butane (CAS 106-97-8) Listed.

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

Propane (CAS 74-98-6) Listed.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Propane (CAS 74-98-6)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Propane (CAS 74-98-6)

US - Texas Effects Screening Levels: Listed substance

2-Methyl-4-isothiazolin-3-one (CAS 2682-20-4) Listed.

Butane (CAS 106-97-8) Listed.

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) Listed.

Propane (CAS 74-98-6) Listed.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

| LEGEND | |
|----------|---|
| Severe | 4 |
| Serious | 3 |
| Moderate | 2 |
| Slight | 1 |
| Minimal | 0 |

| | |
|---------------------|-----|
| HEALTH | / 0 |
| FLAMMABILITY | 4 |
| PHYSICAL HAZARD | 1 |
| PERSONAL PROTECTION | X |



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 20-June-2018

Version # 01

Effective date 20-June-2018

Prepared by
Other information

Dell Tech Laboratories Ltd. Phone: (519) 858-5021

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.