

SECTION 1 — Identification

Product name	Burgundy/Mauve Liquid Dye
Supplier name	Lone Star Candle Supply, Inc.
Recommended use	Compound used in customer substance/mixture/product
Supplier address	5800 Park Vista Circle, Keller, TX 76244
Supplier phone	1-800-929-9425
Emergency phone (24h)	CHEMTREC 1-800-424-9300 / +1 703-741-5970

SECTION 2 — Hazards Identification
2.1. Classification of the substance or mixture
GHS US classification

Hazard class	Category	Hazard statement
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

Hazard pictograms (GHS US):



Signal word (GHS US):	Danger
Hazard statements (GHS US):	H304 - May be fatal if swallowed and enters airways H315 - Causes skin irritation
Precautionary statements (GHS US):	P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves. P301+P310 - If swallowed: Immediately call a doctor, a POISON CENTER. P302+P352 - If on skin: Wash with plenty of water. P321 - Specific treatment (see supplemental first aid instruction on this label). P331 - Do NOT induce vomiting.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 — Composition / Information on Ingredients
3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-methyl derivatives	CAS-No.: 92257-31-3.	12.015 – 32.004	Skin Irrit. 2, H315

Name	Product identifier	%	GHS US classification
Distillates (petroleum), hydrotreated light naphthenic, Baseoil unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]	CAS-No.: 64742-53-6	5.6 – 14.83	Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4 — First-Aid Measures

4.1. Description of necessary first-aid measures

First-aid measures general:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a physician immediately.
First-aid measures after inhalation:	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact:	Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Get medical advice/attention.
First-aid measures after eye contact:	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion:	Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and symptoms:	Based on available data, the classification criteria are not met.
Symptoms/effects after skin contact:	Causes skin irritation.
Symptoms/effects after ingestion:	May be fatal if swallowed and enters airways. Risk of lung edema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment:	Treat symptomatically.
------------------------------------	------------------------

SECTION 5 — Fire-Fighting Measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media:	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire:	Toxic fumes may be released.
---	------------------------------

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions:	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting:	Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 — Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	
-----------------------------	--

Emergency procedures:	Evacuate unnecessary personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
For emergency responders	
Protective equipment:	Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures:	Ventilate area.
Environmental precautions:	Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Notify authorities if product enters sewers or public waters.
6.2. Methods and materials for containment and cleaning up	
Methods for cleaning up:	Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
Other information:	Dispose of materials or solid residues at an authorized site.
See Heading 8,Exposure controls and personal protection,For further information refer to section 13	

SECTION 7 — Handling and Storage

7.1. Precautions for safe handling

Precautions for safe handling:	Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
Hygiene measures:	Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions:	Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store locked up. Store in a well-ventilated place. Keep cool.
Storage area:	Store in a well-ventilated place. Store away from heat.
Incompatible products:	Strong bases. Strong acids.
Incompatible materials:	Sources of ignition. Direct sunlight.
Maximum storage period:	1 year
Storage temperature:	25 °C
Special rules on packaging:	Store in a closed container.
Packaging materials:	Do not store in corrodable metal.

SECTION 8 — Exposure Controls / Personal Protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls:	Ensure good ventilation of the work station.
Environmental exposure controls:	Avoid release to the environment.

8.3. Individual protection measures / Personal protective equipment

Personal protective equipment:	Avoid all unnecessary exposure.
Hand protection:	Wear protective gloves.
Eye protection:	Chemical goggles or safety glasses. Safety glasses
Skin and body protection:	Wear suitable protective clothing
Respiratory protection:	[In case of inadequate ventilation] wear respiratory protection.
PPE symbols:	
Other information:	Do not eat, drink or smoke during use.

SECTION 9 — Physical and Chemical Properties

9.1. Basic physical and chemical properties

Physical state:	Liquid
Color:	Conforms to standard
Odor:	characteristic
Odor threshold:	No data available
pH:	No data available
Melting point:	Not applicable
Freezing point:	No data available
Boiling point:	No data available
Flash point:	> 94 °C
Flammability (solid, gas):	Non flammable.
Vapor pressure:	No data available
Relative vapor density at 20°C:	No data available
Relative density:	No data available
Solubility:	No data available
Partition coefficient n-octanol/water (Log Pow):	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	No data available
Explosion limits:	No data available
Particle characteristics:	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 — Stability and Reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11 — Toxicological Information

11.1. Information on toxicological effects

Acute toxicity (oral): Not classified

Acute toxicity (dermal): Not classified

Acute toxicity (inhalation): Not classified

Distillates (petroleum), hydrotreated light naphthenic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.] (64742-53-6)

LD50 oral rat > 5000 mg/kg (Source: EPA_HP.V)

LD50 dermal rabbit > 2000 mg/kg (Source: EPA_HP.V)

LC50 Inhalation - Rat 2180 mg/m³ (Exposure time: 4 h Source: EPA_HP.V)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Not classified

Respiratory or skin sensitization: Not classified

Germ cell mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive toxicity: Not classified

STOT-single exposure: Not classified

STOT-repeated exposure: Not classified

Aspiration hazard: May be fatal if swallowed and enters airways.

Potential Adverse human health effects and symptoms: Based on available data, the classification criteria are not met.

Symptoms/effects after skin contact: Causes skin irritation.

Symptoms/effects after ingestion: May be fatal if swallowed and enters airways. Risk of lung edema.

SECTION 12 — Ecological Information

12.1. Ecotoxicity

Ecology - general: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute): Not classified

Hazardous to the aquatic environment, long-term (chronic): Not classified

Distillates (petroleum), hydrotreated light naphthenic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.] (64742-53-6)

LC50 - Fish [1] > 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)

EC50 - Crustacea [1] > 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability: Not established.

2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar''-methyl derivatives (92257-31-3)

Persistence and degradability	Not established.
-------------------------------	------------------

Distillates (petroleum), hydrotreated light naphthenic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.] (64742-53-6)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

Bioaccumulative potential:	Not established.
----------------------------	------------------

2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar''-methyl derivatives (92257-31-3)

Partition coefficient n-octanol/water (Log Pow)	> 6.5 (at 30 °C (at pH 6.4)
---	-----------------------------

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone:	Not classified
--------	----------------

Fluorinated greenhouse gases:	No
-------------------------------	----

Other information:	Avoid release to the environment.
--------------------	-----------------------------------

SECTION 13 — Disposal Considerations

Waste treatment methods:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
--------------------------	---

Product/Packaging disposal recommendations:	Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
---	---

Ecological waste information:	Avoid release to the environment. Hazardous waste due to toxicity.
-------------------------------	--

SECTION 14 — Transport Information

In accordance with DOT

14.1. UN number

UN-No. (DOT):	Not applicable
---------------	----------------

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT):	Not applicable
-----------------------------	----------------

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT):	Not applicable
-----------------------------------	----------------

14.4. Packing group

Packing group (DOT):	Not applicable
----------------------	----------------

14.5. Environmental hazards

Other information:	No supplementary information available.
--------------------	---

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT:	Not applicable
------	----------------

SECTION 15 — Regulatory Information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar''-methyl derivatives (92257-31-3.)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated light naphthenic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.] (64742-53-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar''-methyl derivatives (92257-31-3.)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Distillates (petroleum), hydrotreated light naphthenic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.] (64742-53-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar''-methyl derivatives (92257-31-3.)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

Distillates (petroleum), hydrotreated light naphthenic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.] (64742-53-6)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

Listed on Thailand Existing Chemicals Inventory (DIW)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Distillates (petroleum), hydrotreated light naphthenic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.](64742-53-6)	U.S. - Massachusetts - Right To Know List


SECTION 16 — Other Information

Revision date: 2/2/2026

Full text of H-phrases

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation



NFPA health hazard: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard: 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity: 0 - Material that in themselves are normally stable, even under fire conditions.

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Compiled by Lone Star Candle Supply, Inc. (5800 Park Vista Circle, Keller, TX 76244) from supplier-provided information. Section 1 supplier identity and emergency contact standardized to Lone Star; all other section content reproduced from the source SDS.