ASSEMBLY INSTRUCTIONS



REPLACEMENT PARTS

520-812	HOSE, BLAST, BLACK, NOMINAL 3/4" ID x 1-1/2" OD, 2 PLY, WP 150 PSI, PER FOOT
888-2123-106PB	VALVE, AUTO AIR, 1", (NORMALLY CLOSED)
888-2123-00699PB	VALVE, AUTO AIR, 1/2", 3/4" & 1", REPAIR KIT
1431-270	1" SLAVE REGULATOR
1431-270-1	REPAIR KIT FOR 1431-270, 1" SLAVE REGULATOR
1242-250	GAUGE, PRESSURE, 0-160 BACK MNT
888-2125-106PB	MPV, 1", W/URETHANE SLEEVE
888-2125-10099PB	MPV, REPAIR KIT W/URETHANE SLEEVE, INCLUDES PLUNGER
888-2125-10098PB	MPV, SEAL KIT, W/URETHANE SLEEVE
517-271	FILTER, MANUAL 1" NPT MOISTURE TRAP (5 MICRON)
505-161	REPAIR KIT, AIR FILTER, 3/4", 1", 1-1/4" & 1-1/2"
508-002	FILTER ELEMENT 3/4", 1", 1-1/4" & 1-1/2" 5 MICRON
VB100	BALL VALVE, FULL PORT, 1" NPT
1569-4040	VALVE, CONTROL, 4-WAY, PNEU
103-9880	FILTER, 1/4"
1569-3950	VALVE, AIR, DOOR LIMIT
1431-360	REGULATOR, PILOT
408013	PRESSURE GAUGE, 1/8" NPT
120-0260	VALVE, FOOT PEDAL AIR
	888-2123-106PB 888-2123-00699PB 1431-270 1431-270-1 1242-250 888-2125-106PB 888-2125-10099PB 888-2125-10098PB 505-161 505-161 508-002 VB100 1569-4040 103-9880 1569-3950 1431-360 408013



DANGER Explosion Hazard

Opening a pressurized vessel or performing maintenance on pressurized equipment will cause an explosive release of air causing serious injury or death.

Safely depressurize pressure equipment before attempting to open or service. Always disconnect from air source before performing maintenance.



WARNING

These products and equipment are not under any circumstances to be used with sand or silica products of any type and use of such materials will void any warranty. Also, as with the use of any product or equipment you must be sure to use the proper safety equipment and to properly train your employees in the use of any equipment or products. The manufacturer, wholesaler and distributor assume no responsibility arising from the failure to use proper safety equipment or the failure to properly train employees in the use of products and equipment.

