

SECTION 1000-GENERAL SPECIFICATIONS

CARPET CONSTRUCTION SPECIFICATIONS

STYLE.....	STAR TREK 02-B
CONSTRUCTION.....	Multi-Level Loop
FIBER	100% Polypropylene
GAUGE.....	1/10"
STITCHES	10 per inch
PILE HEIGHT	16 oz/yd sq
AVERAGE PILE HEIGHT	3MM +/- 0.5MM
BACKING	BITUMEN
TILE SIZE.....	19.69" X 19.69" (50cm X 50cm)
CARTON QUANTITY.....	5.98 sq. yd (5sqm)
CARTON WEIGHT.....	37.48 lbs. (18.5 kg)
APPROVED INSTALLATION.....	MONOLITHIC - 1/4 TURN - BRICK

CARPET NOTES:

- Every effort is made to ensure that each box shipped meets the highest standards of workmanship and quality. Specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature and humidity, and may vary within normal industry tolerances. Performance is not affected by such variances. Variance may be up to five percent, plus or minus. Quality control tests to accept or reject goods must be performed prior to cutting and installation. No claims for out-of-tolerance material will be accepted after the goods are cut and installed. We reserve the right to change the primary or secondary backing on this carpet without notice where performance is not affected. Due to yarn variations, actual merchandise not guaranteed to exactly color match the sample.
- No claims will be honored if carpet is installed with visible defects.
- **D-E does NOT supply glue** for the carpet. Installers must purchase glue locally or online.
 - Below are 4 recommended adhesives
 - Taylor 2098-Dynamic
 - Dri-Tac ECO-5500
 - AAT-420
 - AAT-520
- Read all instructions prior to beginning any installation.