

SECTION 1000 – GENERAL SPECIFICATIONS

CARPET

The carpet for your new store is a patterned commercial carpet. Therefore, special consideration must be given when choosing a carpet installer. The carpet mill will not honor claims for carpet installed by non-certified installers.

Installation Qualifications: Patterned Carpet Installation should be accomplished by a Floor Covering Installation Board (FCIB) certified firm or an installer who can demonstrate compliance with the FCIB certification program. Call 800-882-8846 for verification or certification. Another option is to visit www.cfinstallers.com Other valid certifications are Floor Covering Installation Contractors Association (FCICA) and the International Certified Floor Covering Installers Association (CFI). The installer must meet or exceed C-1 or C-2 classification.

CARPET CONSTRUCTION SPECIFICATIONS

STYLE	SARDANGNA 16
CONSTRUCTION	Multi-Level Loop
FIBER.....	100% Polypropylene
GAUGE.....	1/10"
STITCHES	10 per inch
PILE HEIGHT.....	16 oz/yd sq
AVERAGE PILE HEIGHT	3MM +/- 0.5MM
BACKING.....	BITUMEN
TILE SIZE	19.69" X 19.69" (50cm X 50cm)
CARTON QUANTITY	5.98 sq. yd (5sqm)
CARTON WEIGHT	37.48 lbs. (18.5 kg)
APPROVED INSTALLATION	MONOLITHIC - 1/4 TURN - BRICK

SECTION 1000-GENERAL SPECIFICATIONS

CARPET NOTES:

- Every effort is made to insure that each box shipped meets the highest standards of workmanship and quality. Specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature and humidity, and may vary within normal industry tolerances. Performance is not affected by such variances. Variance may be up to five percent, plus or minus. Quality control tests to accept or reject goods must be performed prior to cutting and installation. No claims for out-of-tolerance material will be accepted after the goods are cut and installed. We reserve the right to change the primary or secondary backing on this carpet without notice where performance is not affected. Due to yarn variations, actual merchandise not guaranteed to exactly color match the sample.
- No claims will be honored if carpet is installed with visible defects.
- D-E **does NOT supply glue** for the carpet. Installers must purchase glue locally or online.
 - Below are 4 recommended adhesives
 - Taylor 2098-Dynamic
 - Dri-Tac ECO-5500
 - AAT-420
 - AAT-520
- Read all instructions prior to beginning any installation.