

SECTION 1000-GENERAL SPECIFICATIONS

SLATWALL SPECIFICATIONS

Plato's Closet uses a specialty slatwall –available through D-E only.

Slatwall used in **Plato's Closet** stores must be 115 pounds internal bond or better and with a density of 47 pounds per cubic foot. It must be ¾" thick, measuring 48" x 96". The grooves are to be 6" center to center running the 96" length w/Metal Inserts. **DO NOT use Home Improvement Centers grade of Slatwall.**

MATERIALS

SUBSTRATES: MDF (Medium Density Fiberboard) conforming to ANSI A208.2, industrial-grade MDF or other wood fibers substrates having not less than 75% recycled wood waste.

FORMALDEHYDE: Slatwall panels shall have formaldehyde emissions of 0.3 PPM or less and shall comply with HUD 24 CFR Part 3280 Standards set fourth for particleboard panels.

FIRE RATING: Our slatwall products meet a class "C" rating as determined by standard ASTM E-84 Standard Test Method for Surface Burning Characteristics of Burning Materials.

**Check with local building codes to verify that a higher-class fire rating is not required.*

FINISH: High Pressure Laminate: Vertical grade 0.030" thick high pressure plastic laminate adhered to wood fiber substrate by cold pressing polyvinyl acetate (PVA) type II, water resistant adhesives.

1. Edges-Square, and sealed, to provide a black edge
2. Balancing Backer: Kraft Paper that does not contribute to or pose an unusual additional fire hazard.
3. Color: Amarena & Storm

Low Pressure Laminate (Melamine treated paper) bonded to wood fiber substrate by hot melt adhesive. Color: Reface Black

PANEL SIZE

Standard panel sizes are 4' x 8'; horizontal grooves with metal inserts, run 8' length. Slat spacing is 6" on center.