

SECTION 1000-GENERAL SPECIFICATIONS

COMPUTER

NETWORK CABLE:

Enclose as much of the cable as possible in PVC pipe to protect it from wear. If network cable gets stepped on, wet or kinked, there is a very good possibility it will not work. Do not run the cable through the same conduit as electrical or telephone wire. This could cause interference in the computer network. If the cable needs to be run across the ceiling, keep the cable at least 6 feet from fluorescent lights. If you must cross fluorescent lights, do so at a 90-degree angle.

POWER:

The computer outlet should be a dedicated 20A circuit with isolated ground, orange in color, to distinguish it from the others. If you have a computer in an office or other workstation away from your main P.O.S. counter, they should be on the same circuit. If your computer is not plugged into a battery backup unit, you need to have the computer, monitor and printers plugged into a surge strip designed for computer equipment. The computer with your modem should have a phone surge plug as well.

PAINT

Paint is Sherwin Williams brand and is to be purchased by the store owner.

- Morris Room Gray #SW0037 semi-gloss or eggshell (wall behind P.O.S.)
- Natural Choice #SW7011 semi-gloss or eggshell (all non-P.O.S. and non-Focus Area)
- Porpoise #SW7047 semi-gloss or eggshell (Focus Area)

**Paint doors and door frames the same color as corresponding walls.

***See your elevation drawings (F2) for specific directions for your store

CARPET

The carpet for your new store is a patterned commercial carpet. Therefore, special consideration must be given when choosing a carpet installer. The carpet mill will not honor claims for carpet installed by non-certified installers.

Installation Qualifications: Patterned Carpet Installation should be accomplished by a Floor Covering Installation Board (FCIB) certified firm or an installer who can demonstrate compliance with the FCIB certification program. Call 800-882-8846 for verification or certification. Another option is to visit www.cfiinstallers.com Other valid certifications are Floor Covering Installation Contractors Association (FCICA) and the International Certified Floor Covering Installers Association (CFI). The installer must meet or exceed C-1 or C-2 classification.

SECTION 1000-GENERAL SPECIFICATIONS

CARPET CONSTRUCTION SPECIFICATIONS

STYLE.....	Still S4009 1615 Hush
CONSTRUCTION.....	Tufted
FIBER	100% Solution Dyed Nylon
GAUGE.....	1/10
STITCHES	11 per inch
PILE HEIGHT	Average .114"
TUFTER PILE WEIGHT.....	18 oz per sq. yd.
PRIMARY BACKING	100% Synthetic
TILE SIZE.....	24" x 24"
CARTON QUANTITY	8.0 sq yd
CARTON WEIGHT.....	40.78 lbs. (18.5 kg)
APPROVED INSTALLATION.....	1/4 TURN – Ashlar vertical /Horizontal
WARRANTIES.....	Limited Lifetime Carpet Tile Warranty, including wear Delamination, Tuft Bind, Edge Ravel and Static Protection

CARPET NOTES:

- Every effort is made to ensure that each box shipped meets the highest standards of workmanship and quality. Specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature and humidity, and may vary within normal industry tolerances. Performance is not affected by such variances. Variance may be up to five percent, plus or minus. Quality control tests to accept or reject goods must be performed prior to cutting and installation. No claims for out-of-tolerance material will be accepted after the goods are cut and installed. We reserve the right to change the primary or secondary backing on this carpet without notice where performance is not affected. Due to yarn variations, actual merchandise not guaranteed to exactly color match the sample.
- No claims will be honored if carpet is installed with visible defects.
- D-E **does NOT supply glue** for the carpet. Installers must purchase glue locally or online.
 - Signature 3000 Premium Pressure Sensitive Adhesive
- Read all instructions prior to beginning any installation:
 - <https://www.signatureflooring.com/wp-content/uploads/2019/07/Carpet-Tile-Installation-Guide.pdf>
 - [Regular Care and Maintenance:](#)
 - <https://www.signatureflooring.com/wp-content/uploads/2019/07/LVT-Glue-Down-Care-Maintenance.pdf>