

SECTION 1000-GENERAL SPECIFICATIONS

VINYL PLANK FLOOR

VINYL PLANK CONSTRUCTION SPECS:

STYLE.....	Opus
COLOR	Bleached Walnut WP329
DIMENSIONS	36" x 6"
THICKNESS	2.5mm
WEAR LAYER	20 mil
BEVELED EDGE.....	Micro
BOX QUANTITY	36 sq. ft

1009.2- WOOD PLANK PERFORMANCE TESTING:

CLASSIFICATIONS.....	ASTM F1700
FIRE RESISTANCE.....	ASTM E648-06 CLASS 1
SLIP RESISTANCE.....	ASTM D2047
SUITABILITY.....	Commercial heavy duty, suitable for most retail, commercial and domestic applications.
RECYCLING.....	Suitable
ADHESIVE.....	Dry Set / K-Spray / Karndean Epoxy / K-95HM
WARRANTY.....	Commercial Warranty: 15 years

Karndean Limited Warranty

This warranty does not include the following:

1. damage due to: stains, burns, cuts, gouges, scuffs, scratches, indentations, and other accidents or abuse;
2. discoloration or bond release from hydrostatic pressure or excessive moisture caused by such things as flooding, plumbing and appliance leaks;
3. installation of flooring over particle board, chip wood, or press wood;
4. installation where material was not installed with Karndean adhesive in accordance with Karndean specifications and recommended usage;
5. dissatisfaction due to improper installation, maintenance or irregularities;
6. reductions in gloss or buildup of residue due to improper maintenance or normal wear and gloss reduction from use.

SECTION 1000-GENERAL SPECIFICATIONS

Additional Karndean Flooring Details

Installation Guide :

<https://www.karndean.com/en/floors/resources/brochures-and-guides/installation-guides/>

➡ Glue down Installation Guide

➡ *Download Installation Guide

*Otherwise, each box has the installation instructions printed off for easy viewing.

Commercial Cleaning & Maintenance:

<https://www.karndean.com/en/floors/resources/cleaning-and-maintenance/>