

SECTION 1000-GENERAL SPECIFICATIONS

PAINT

All interior retail walls, including slatwall and furring strips are to be painted:

- Sherwin Williams #6301 Patient White and Sherwin Williams #6234 Uncertain Gray, ProMar 200 Zero VOC Interior Latex, semi-gloss finish. Refer to F2 "Wall Elevation" for exact color location.

The bathroom walls are to be painted either:

- Sherwin Williams #6301 Patient White or Sherwin Williams #6234 Uncertain Gray, ProMar 200 Zero VOC Interior Latex, semi-gloss finish.

All interior doors, door jambs, door frames, are to be painted:

- Sherwin Williams #6126 Navajo White ProMar 200 Zero VOC Interior Latex, semi-gloss finish.

All open ceilings should be painted:

- Sherwin Williams #6126 Navajo White ProMar 200 Zero VOC Interior Latex, semi-gloss finish.

WIRE GRID

Wire grid panels, for use in the **Once Upon a Child** stores, should be 3-inch center to center squares of powder coated **white grid**.

All 2' x 4', 2' x 5', 2' x 6', 2' x 7' and 4' x 4' wire grid panels are to have double wire at long dimensions.

CABINET REFACING SLATWALL SPECIFICATIONS

Slatwall used on the front of the cabinets in **Once Upon a Child** stores' must be 115 pounds internal bond or better and with a density of 47 pounds per cubic foot. It must be $\frac{3}{4}$ " thick, measuring 48" x 96". The grooves are to be 6" center to center running the 96" length.

Finish is to be paint grade.

DO NOT use Home Improvement Center stores grade of slatwall.

MATERIALS

SUBSTRATES: MDF (Medium Density Fiberboard) conforming to ANSI A208.2, industrial-grade MDF or other wood fibers substrates having not less than 75% recycled wood waste.

FORMALDEHYDE: Slatwall panels shall have formaldehyde emissions of 0.3 PPM or less and shall comply with HUD 24 CFR Part 3280 Standards set fourth for particleboard panels.

FIRE RATING: Our slatwall products meet a class "C" rating as determined by ASTM E-84

**Check with local building codes to verify that a higher-class fire rating is not required.*

FINISH: Low-Pressure Laminate (Melamine treated paper) bonded to wood fiber substrate by hot melt adhesive. Color: Blue Lapis, North Sea & Island

PANEL SIZE: Standard panel sizes are 4' x 8'; horizontal grooves run 8' length. Slat sizing 6" on center.